

What is claimed is:

1. A material for a thermal fuse element wherein said material has an alloy composition in which Sn is larger than 46% and 70% or smaller, Bi is 1% or larger and 12% or smaller, and In is 18% or larger and smaller than 48%.  
5
2. A material for a thermal fuse element wherein 0.1 to 3.5 weight parts of one, or two or more elements selected from the group consisting of Ag, Au, Cu, Ni, Pd, Pt, Sb, Ga, and Ge are added to 100 weight parts of an alloy composition of  
10 claim 1.
3. An alloy type thermal fuse wherein a material for a thermal fuse element of claim 1 is used as a fuse element.
4. An alloy type thermal fuse wherein a material for a thermal fuse element of claim 2 is used as a fuse element.
- 15 5. An alloy type thermal fuse according to claim 3, wherein said fuse element contains inevitable impurities.
6. An alloy type thermal fuse according to claim 4, wherein said fuse element contains inevitable impurities.
7. An alloy type thermal fuse according to claim 3, wherein  
20 said fuse element is connected between lead conductors, and at least a portion of each of said lead conductors which is bonded to said fuse element is covered with an Sn or Ag film.
8. An alloy type thermal fuse according to claim 4, wherein  
25 said fuse element is connected between lead conductors, and

at least a portion of each of said lead conductors which is bonded to said fuse element is covered with an Sn or Ag film.

9. An alloy type thermal fuse according to claim 5, wherein  
5 said fuse element is connected between lead conductors, and at least a portion of each of said lead conductors which is bonded to said fuse element is covered with an Sn or Ag film.

10. An alloy type thermal fuse according to claim 6, wherein said fuse element is connected between lead conductors, and at least a portion of each of said lead conductors which is bonded to said fuse element is covered with an Sn or Ag film.

11. An alloy type thermal fuse according to claim 3,  
15 wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of  
20 said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

12. An alloy type thermal fuse according to claim 4, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse ele-  
25 ment, said flux-applied fuse element is passed through a

cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

- 5 13. An alloy type thermal fuse according to claim 5, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

14. An alloy type thermal fuse according to claim 6, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

15. An alloy type thermal fuse according to claim 7, wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical

case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

16. An alloy type thermal fuse according to claim 8,  
5 wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of  
10 said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

17. An alloy type thermal fuse according to claim 9,  
wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse ele-  
15 ment, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical case and said lead conductors are sealingly closed, ends of said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

20 18. An alloy type thermal fuse according to claim 10,  
wherein lead conductors are bonded to ends of said fuse element, respectively, a flux is applied to said fuse element, said flux-applied fuse element is passed through a cylindrical case, gaps between ends of said cylindrical  
25 case and said lead conductors are sealingly closed, ends of

said lead conductors have a disk-like shape, and ends of said fuse element are bonded to front faces of said disks.

19. An alloy type thermal fuse according to claim 3, wherein a pair of film electrodes are formed on a substrate  
5 by printing conductive paste containing metal particles and a binder, said fuse element is connected between said film electrodes, and said metal particles are made of a material selected from the group consisting of Ag, Ag-Pd, Ag-Pt, Au, Ni, and Cu.

10 20. An alloy type thermal fuse according to claim 4, wherein a pair of film electrodes are formed on a substrate by printing conductive paste containing metal particles and a binder, said fuse element is connected between said film electrodes, and said metal particles are made of a material  
15 selected from the group consisting of Ag, Ag-Pd, Ag-Pt, Au, Ni, and Cu.

21. An alloy type thermal fuse according to claim 5, wherein a pair of film electrodes are formed on a substrate by printing conductive paste containing metal particles and  
20 a binder, said fuse element is connected between said film electrodes, and said metal particles are made of a material selected from the group consisting of Ag, Ag-Pd, Ag-Pt, Au, Ni, and Cu.

22. An alloy type thermal fuse according to claim 6,  
25 wherein a pair of film electrodes are formed on a substrate

by printing conductive paste containing metal particles and a binder, said fuse element is connected between said film electrodes, and said metal particles are made of a material selected from the group consisting of Ag, Ag-Pd, Ag-Pt, Au, Ni, and Cu.

23. An alloy type thermal fuse according to claim 3, wherein a heating element for fusing off said fuse element is additionally disposed.

24. An alloy type thermal fuse according to claim 4, wherein a heating element for fusing off said fuse element is additionally disposed.

25. An alloy type thermal fuse according to claim 5, wherein a heating element for fusing off said fuse element is additionally disposed.

26. An alloy type thermal fuse according to claim 6, wherein a heating element for fusing off said fuse element is additionally disposed.

27. An alloy type thermal fuse according to claim 7, wherein a heating element for fusing off said fuse element is additionally disposed.

28. An alloy type thermal fuse according to claim 8, wherein a heating element for fusing off said fuse element is additionally disposed.

29. An alloy type thermal fuse according to claim 9, wherein a heating element for fusing off said fuse element

is additionally disposed.

30. An alloy type thermal fuse according to claim 10,  
wherein a heating element for fusing off said fuse element  
is additionally disposed.

5 31. An alloy type thermal fuse according to claim 11,  
wherein a heating element for fusing off said fuse element  
is additionally disposed.

32. An alloy type thermal fuse according to claim 12,  
wherein a heating element for fusing off said fuse element  
10 is additionally disposed.

33. An alloy type thermal fuse according to claim 13,  
wherein a heating element for fusing off said fuse element  
is additionally disposed.

34. An alloy type thermal fuse according to claim 14,  
15 wherein a heating element for fusing off said fuse element  
is additionally disposed.

35. An alloy type thermal fuse according to claim 15,  
wherein a heating element for fusing off said fuse element  
is additionally disposed.

20 36. An alloy type thermal fuse according to claim 16,  
wherein a heating element for fusing off said fuse element  
is additionally disposed.

37. An alloy type thermal fuse according to claim 17,  
wherein a heating element for fusing off said fuse element  
25 is additionally disposed.

38. An alloy type thermal fuse according to claim 18, wherein a heating element for fusing off said fuse element is additionally disposed.

39. An alloy type thermal fuse according to claim 19,  
5 wherein a heating element for fusing off said fuse element is additionally disposed.

40. An alloy type thermal fuse according to claim 20, wherein a heating element for fusing off said fuse element is additionally disposed.

10 41. An alloy type thermal fuse according to claim 21, wherein a heating element for fusing off said fuse element is additionally disposed.

42. An alloy type thermal fuse according to claim 22, wherein a heating element for fusing off said fuse element  
15 is additionally disposed.

43. An alloy type thermal fuse according to claim 3, wherein a pair of lead conductors are partly exposed from one face of an insulating plate to another face, said fuse element is connected to said lead conductor exposed portions, and said other face of said insulating plate is covered with an insulating material.  
20

44. An alloy type thermal fuse according to claim 4, wherein a pair of lead conductors are partly exposed from one face of an insulating plate to another face, said fuse  
25 element is connected to said lead conductor exposed por-



tions, and said other face of said insulating plate is covered with an insulating material.

45. An alloy type thermal fuse according to claim 5, wherein a pair of lead conductors are partly exposed from one face of an insulating plate to another face, said fuse element is connected to said lead conductor exposed portions, and said other face of said insulating plate is covered with an insulating material.

46. An alloy type thermal fuse according to claim 6, wherein a pair of lead conductors are partly exposed from one face of an insulating plate to another face, said fuse element is connected to said lead conductor exposed portions, and said other face of said insulating plate is covered with an insulating material.

47. An alloy type thermal fuse according to claim 7, wherein a pair of lead conductors are partly exposed from one face of an insulating plate to another face, said fuse element is connected to said lead conductor exposed portions, and said other face of said insulating plate is covered with an insulating material.

48. An alloy type thermal fuse according to claim 8, wherein a pair of lead conductors are partly exposed from one face of an insulating plate to another face, said fuse element is connected to said lead conductor exposed portions, and said other face of said insulating plate is covered with an insulating material.

ered with an insulating material.

49. An alloy type thermal fuse according to claim 9,  
wherein a pair of lead conductors are partly exposed from  
one face of an insulating plate to another face, said fuse  
5 element is connected to said lead conductor exposed por-  
tions, and said other face of said insulating plate is cov-  
ered with an insulating material.

50. An alloy type thermal fuse according to claim 10,  
wherein a pair of lead conductors are partly exposed from  
10 one face of an insulating plate to another face, said fuse  
element is connected to said lead conductor exposed por-  
tions, and said other face of said insulating plate is cov-  
ered with an insulating material.

51. An alloy type thermal fuse according to claim 3,  
15 wherein said fuse element connected between a pair of lead  
conductors is sandwiched between insulating films.

52. An alloy type thermal fuse according to claim 4,  
wherein said fuse element connected between a pair of lead  
conductors is sandwiched between insulating films.

20 53. An alloy type thermal fuse according to claim 5,  
wherein said fuse element connected between a pair of lead  
conductors is sandwiched between insulating films.

54. An alloy type thermal fuse according to claim 6,  
wherein said fuse element connected between a pair of lead  
25 conductors is sandwiched between insulating films.

55. An alloy type thermal fuse according to claim 7, wherein said fuse element connected between a pair of lead conductors is sandwiched between insulating films.

56. An alloy type thermal fuse according to claim 8,  
5 wherein said fuse element connected between a pair of lead conductors is sandwiched between insulating films.

57. An alloy type thermal fuse according to claim 9, wherein said fuse element connected between a pair of lead conductors is sandwiched between insulating films.

10 58. An alloy type thermal fuse according to claim 10, wherein said fuse element connected between a pair of lead conductors is sandwiched between insulating films.